

LSP-SGP401

Desktop Small Box NIC Module With 4 Pairs Of 10G/1G/100M LAN Ports &10KV Surge Protection



■ Features

- 4x LAN Pairs Or 3x LAN Pairs & 1x Console Pair
- Up To 10KV Surge Protection
- -40°C~85°C Operating Range

■ Specifications

4x Pairs surge protection Desktop Small Box.		
SKU	LSP-SGP401A	LSP-SGP401B
Interface		
Connector	4x Pairs RJ45 Ethernet w/o LED (4x input, 4x output)	3x Pairs RJ45 Ethernet and 1x Pairs RJ45Console w/o LED (4x input, 4x output)
Data Line Protection	RJ-45 10G/1G/100M Ethernet <i>In 10G set-up, it can only support up to 50m long cable</i>	
ESD/Surge Protection	Absorbing Transient Current with Response to surge voltage up to 10KV ESD contact :8KV Air: 15KV	
Surge Protection		
POE surge protection	Yes, support IEEE 802.3af 15.4W; IEEE802.3at 30W	
Service Voltage	58VDC	
Protection Mode	Common Mode (All) Differential Mode (All)	
Surge Current Rating Line to GND (CM)	10kV @ 10/700µs / LAN Pair	10kV @ 10/700µs / LAN Pair 8kV @ 1.2/50µs / Console pair
Surge Current Rating Line to Line (DM)	2kV @ 10/700µs / LAN Pair	2kV @ 10/700µs / LAN Pair 8kV @ 1.2/50µs / Console pair
System Compatibility		
	Lanner Network Appliance	
Temperature		
Operating	Operating: -40°C~85°C	
Humidity		
	95% Non-condensing	
Mechanical		
Dimension (W x D x H)	100 X 120 X 40 mm	
Weight	460g	

■ Ordering Information

LSP-SGP401A	4 LAN Pairs With 10kv Surge Protection Desktop Small Box
LSP-SGP401B	3 LAN Pairs With 10kv Surge Protection & 1 Console Pair 8kv Desktop Small Box

LSP-SGP401

NIC Module